

PNEUMATIC COUPLINGS
PNEUMATISCHE KUPPLUNGEN

SERIE 027

SUPER FLOW **SUPERDURCHFLUSS**



Couplers and Plugs
Kupplungen und Nippel


Connection
Anschlüsse

Order No
Bestellnr.

SW


L

ØD




Male Thread Coupling
Kupplungen mit Aussengewinde

BSPT 1/4"	027 RG 13	19	60	23
BSPT 3/8"	027 RG 17	19	60	23
BSPT 1/2"	027 RG 21	22	60	23
BSPT 3/4"	027 RG 26	60	60	23
BSP 1/4"	027 EG 13	19	60	23
BSP 3/8"	027 EG 17	19	60	23
BSP 1/2"	027 EG 21	22	60	23
BSP 3/4"	027 EG 26	60	60	23




Female Thread Coupling
Kupplung mit Innengewinde

BSP 1/4"	027 DG 13	19	56	23
BSP 3/8"	027 DG 17	19	55	23
BSP 1/2"	027 DG 21	24	58	23
NPT 1/4"	027 TG 13	19	56	23
NPT 3/8"	027 TG 17	19	55	23
NPT 1/2"	027 TG 21	24	58	23




Standard Hose Barb Coupling
Kupplung mit Schlauchtülle

6 mm - 1/4"	027 HG 06	19	74	23
8 mm - 5/16"	027 HG 08	19	74	23
9 mm - 5/14"	027 HG 09	19	74	23
10 mm - 3/8"	027 HG 10	19	74	23
13 mm - 1/2"	027 HG 13	19	74	23




Standard Hose Barb Plug
Nippel mit Schlauchtülle

6 mm - 1/4"	027 HU 06		48	12
8 mm - 5/16"	027 HU 08		48	12
9 mm - 5/14"	027 HU 09		48	12
10 mm - 3/8"	027 HU 10		48	12
13 mm - 1/2"	027 HU 13		48	15



Male Thread Plug
Nippel mit Aussengewinde

BSPT 1/8"	027 RU 10	13	33	
BSPT 1/4"	027 RU 13	14	37	
BSPT 3/8"	027 RU 17	17	37	
BSPT 1/2"	027 RU 21	22	43	
BSP 1/8"	027 EU 10	13	33	
BSP 1/4"	027 EU 13	17	37	
BSP 3/8"	027 EU 17	17	37	
BSP 1/2"	027 EU 21	22	43	



Female Thread Plug
Nippel mit Innengewinde

BSP 1/4"	027 DU 13	17	33	
BSP 3/8"	027 DU 17	19	33	
BSP 1/2"	027 DU 21	24	36	

Interchangeability - Kompatibilität
RECTUS 27, CEJN 410, TST 410

Temperature Range - Temperaturbereich
-20°C +100°C (-4°F +212°F)

Working Pressure - Betriebsdruck
0 - 35 bar (0 - 508 PSI)

Flow capacity - Nennweite
NW - 10

Option - Optionen

F - Straight through flow - ungehinderter Durchfluss
S - Stainless Steel - Edelstahl
V - Viton Seal - Viton Dichtung

For optional orders please add the symbol of your option end of the order no.

Bei Optionsbestellungen Kennbuchstabe bitte hinzufügen (Beispiel: 027 RG 13-K-V)

Material - Material

Coupler Body -
Kupplungsgrundkörper: Brass Nickel Plated - Messing vernickelt

Back Part -
Hinterteil : Brass Nickel Plated - Messing vernickelt

Sleeve - Hülse : Steel Nickel Plated - Stahl vernickelt

Valve - Ventil : Brass - Messing
Springs - Federn : Stainless Steel - Edelstahl

Balls - Kugeln : Stainless Steel - Edelstahl AISI 420

Seals - Dichtungen : Nitrile (Ni) - NBR (Ni)

Plug - Nippel : Steel Nickel Plated - Stahl vernickelt

